

SX-3000

Standalone Integrated Media Block™ with Portable Storage

Every function you could possibly wish for your digital cinema in a single media block with versatile storage solution



SX-3000 Standalone IMB®



Portable Storage

“ The SX-3000 Standalone Integrated Media Block™ (“SX-3000 Standalone IMB®”) comes with Portable Storage, a cost effective, reliable and scalable external storage solution. Portable Storage is a compact and lightweight device that can be mounted on all types of DLP Cinema® projectors and features up to 3TB of hot swappable storage. ”

Why choose GDC Technology's SX-3000 IMB with Portable Storage ?

SX-3000 **Standalone IMB**®

1

Lower Maintenance Costs

The SX-3000 IMB eliminates the need for an external file server. It seamlessly integrates with all DLP Cinema® projectors and comes with SMS software for playback control and content management.

2

Lower Operation Costs

The SX-3000 IMB allows long distance content streaming and remote access via gigabit Ethernet connection. Also automation can be controlled via Ethernet cable which makes SX-3000 IMB with Portable Storage suitable for boothless design.

3

High Frame Rate and All Image Resolution Support

The SX-3000 IMB supports high frame rate content in 2D and 3D (48 & 60fps per eye) and all image resolution including SD, HD, 2K and 4K (optional)..

4

Comprehensive Support for Alternative Content

The SX-3000 IMB supports HDMI input, 3G-SDI input and network live streaming¹ (optional). It also supports image scaling to 2K.

5

Live 3D Support¹ (Optional)

The SX-3000 IMB comes integrated with 3D Demuxing (side-by-side) which makes receiving high-quality 3D broadcasts possible. It also provides a built-in integrated 3D decoder to seamlessly support 3D Live broadcast without requiring additional decoder.

6

Up to 3TB Storage²

The Portable Storage is scalable with different options. It can support up to 3TB of redundant hot swappable storage, which can store approximately 30 movies (i.e. 100GB per movie).

7

High Reliability

The Portable Storage comes with 3 or 4 hot swappable data drives² and is based on enterprise hardware RAID 5 technology allowing it to remain operational in the event of a single drive failure, thereby minimizing downtime.

8

High Flexibility

The Portable Storage comes with hot swappable data drives that can easily be attached or detached, making it possible to quickly switch content from one screen to another.


9

Easy Installation

The Portable Storage is a very compact and light external storage device which can be easily mounted on projectors, making it suitable for boothless cinema design.




System Configuration




Technical Drawing SX-3000 IMB


Front View



Top View




Side View




Portable Storage

Front View



Side View



Top View



Technical Specifications

Physical

Dimensions (IMB)	320(W) x 240(D) x 63.7(H) mm
Dimensions (Portable Storage)	220(W) x 165.6 (D) x 55.2 (H) mm
Weight (IMB)	1.5 kg
Weight (Portable Storage)	1 kg excluding hard disk

Environmental

Operating temperature	0°C to 40°C (0°F to 104°F)
Operating humidity	20% to 90%, non-condensing
Operating altitude	10,000 ft (3,000m) above sea level ³

Power

Power requirement	100 to 240V, 60 to 50Hz, 1.4A
Max power consumption (IMB)	75W
Max power consumption (Portable Storage)	30W

Video Specifications

JPEG 2000	4K – 24 (2D) (optional) 2K – 24, 48, 60 (2D) 2K – 24, 48, 60 (3D)
MPEG 2/MPEG 4 ⁴	SD/HD
Packaging	SMPT Digital Cinema Package (DCP), Interop DCP

Audio Output

Digital uncompressed audio	16/24-bit AES/EBU, 16 channels, 48/96 KHz 2 x RJ45
----------------------------	--

System Interfaces

Ethernet	2 x RJ-45 (1000 BaseT)
eSATA	x 3
USB2.0	2 x USB A-Type Female
LTC	In & Out (2 x BNC)
REF	Passive loop output / Video sync input (2 x BNC)
HDMI	x 1 (alternative content input)
3G-SDI	x 2 (alternative content input)
8-port GPIOs (optional)	4 x RJ45 (8 GPIOs and 8 GPOs)

Storage options

Redundant hot swappable 2TB or 3TB

Security

AES 128-bit encrypted data storage
Civolution (NexGuard[®]) forensic
watermarking

Subtitles

Subtitle overlay⁴
Projector Cinecanvas support

User Interface

PC/ Mac/ VGA

Third-party Integration Options

TMS	GDC, Third-party ⁵
3D system	RealD, Dolby 3D, MasterImage, active systems
4D system	D-BOX Motion Code™, 4D plex
3D sound	Dolby Atmos ⁴
Closed Captioning Device	Support SMPTE430-10

¹ Depending on specifications – please check with GDC Technology sales representatives.

² Depending on storage option – please check with GDC Technology sales representatives.

³ Depending on specifications of the hard disk

⁴ Feature may not be available upon initial release

⁵ Please check with your TMS provider

GDC Technology Offices

Hong Kong (Headquarters)

Unit 1-7, 20th Floor,
Kodak House II,
39 Healthy Street East,
North Point, Hong Kong
Tel : +852 2507 9555

China (Beijing)

Rm. 609-618, Office Building,
20# Xinde Street,
Xicheng District,
Beijing, P.R. China 100088
Tel : +86 10 6205 7040

China (Shenzhen)

Room A701, 7/F,
Languang Technology Building,
No.7 Xinxu Road,
North Zone,
Hi-Tech Park,
Nanshan District,
Shenzhen, P.R. China
Tel : +86 755 8608 6000

Spain (Barcelona)

Edificio Mercurio,
Vía Augusta, 59, desp. 607,
08006 Barcelona, Spain
Tel : +34 93 159 51 75

Peru (Lima)

Calle Rey Bahamonde N°111,
Santiago de Surco,
Lima 33 - Peru
Tel : +51 1 677 6708

USA (Los Angeles)

1016 West Magnolia Boulevard,
Burbank, CA 91506, USA
Tel : +1 818 972 4370 /
+1 877 743 2872 (Toll Free)

Singapore

10 Ubi Crescent,
Ubi Tech Park,
Lobby B, #06-25,
Singapore 408564
Tel : +65 6222 1082

Indonesia (Jakarta)

Total Building Lantai 4 Suite 0401,
Jl. Letjen S. Parman Kav. 106A,
Kel. Tomang,
Kec. Grogol Petamburan,
Jakarta Barat 11440

Japan (Tokyo)

3F, Kyobashi-Chuo Bldg,
1-14-7 Kyobashi Chuo-ku,
Tokyo 104-0031, Japan
Tel : +81 3 5524 3607

India (Mumbai)

Office No. B-207/208,
Everest Chamber,
Andheri Kurla Road,
Marol, Andheri (East),
Mumbai, 400059, India
Tel : +91 22 4044 0500

Mexico (Mexico City)

Ave. Santa Fe 94,
Torre A Piso 8,
Col. Zedec Santa Fe,
Alvaro Obregon,
Mexico, D.F.,
C.P. 01210 Mexico
Tel : +52 55 8851 1198 /
+52 55 8851 1165

Email : info@gdc-tech.com

Website : www.gdc-tech.com



GDC Technology manufacturing facility is ISO 9001 : 2008 certified.

Copyright © 2015 GDC Technology Limited. All rights reserved. All trademarks listed in this brochure are properties of their respective owners. Specifications are subject to change without notice due to ongoing product development and improvement.